



CRYICECUBEWWKIT

3W 3000K Warm White Quicklink: Q21BC

General

Colour Chrome,Clear
Construction Aluminium / Glass

Dimmable Yes IP Rating IP55

Dimmable Yes

Dimensions

Cut Out 23mm (Diameter)

Depth 41mm Length 109mm Minimum Ceiling 68mm

Depth

Width 40mm

Electrical

Amperage 700mA Maximum Wattage 3W

Light Characteristics

Beam Angle 15° Colour Rendering 80

Index

Colour Temperature 3000K Warm White

Lumens Per Watt 51 lm/W



The **Crystal Ice Cube** is a decorative LED downlight made from cut glass with a chrome finish base. When illuminated the different facets cast a pattern of light back on to the surface into which the downlight is recessed. The result is a stylish and elegant lighting effect.

The fitting comes with a ceiling spring for fixing into plaster board. A burial tube is supplied for recessing into more solid material, such as brick or concrete.

An LED driver is needed to power this product.

LED Driver Options

- LED Driver (Switching) Use this driver for on/off control. Cannot be used for dimming.
- LED Driver (Dimming) For use with nearly all domestic dimming lighting. Most resistive dimmers have a minimum load of 60W, therefore ensure that if this not met, a dummy load is added to the circuit, such as a mains voltage halogen fitting.
- LED Driver (1-10V) For use with 1-10V dimmer modules or 1-10V control systems. This type of dimming does not have a minimum load.
- Wise Scene (Dimming + Wireless) This controller can be used for both switching and dimming. Additionally, this unit can communicate via radio and external push buttons, allowing you to wirelessly control your fitting. Note that an additional 24V LED driver is required to power the Wise Scene pack.