



CRYICESTARSMCWKIT

3W 4000K Cool White
Quicklink: Q21C1

General	
Colour	Chrome,Clear
Construction	Aluminium / Glass
Dimmable	Yes
IP Rating	IP55
Dimmable	Yes
Dimensions	
Cut Out	23mm (Diameter)
Depth	16mm
Length	84mm
Minimum Ceiling Depth	68mm
Width	29mm
Electrical	
Amperage	700mA
Maximum Wattage	3W
Light Characteristics	
Beam Angle	15°
Colour Rendering Index	75
Colour Temperature	4000K Cool White
Lumens	205 lm
Lumens Per Watt	68 lm/W

The **Crystal Icestar Small** is a decorative LED downlight made from cut glass with a chrome finish base. When illuminated the different facets cast a pattern of light back on to the surface into which the downlight is recessed. The result is a stylish and elegant lighting effect.

The fitting comes with a ceiling spring for fixing into plaster board. A burial tube is supplied for recessing into more solid material, such as brick or concrete.

An LED driver is needed to power this product.

LED Driver Options

- Switching - Use this driver for on/off control. Cannot be used for dimming.
- Dimming - Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
- Dimming - 1-10V - Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.