



## CRY STARLITE W/W

1W 3000K Warm White  
Quicklink: Q21DB

### General

Colour	Chrome, Clear
Construction	Aluminium / Glass
Dimmable	Yes
IP Rating	IP55

Dimmable Yes

### Dimensions

Cut Out	14mm (Diameter)
Depth	11mm
Length	69mm
Minimum Ceiling Depth	58mm
Width	20mm

### Electrical

Amperage	350mA
Maximum Wattage	1W

### Light Characteristics

Beam Angle	15°
Colour Rendering Index	80
Colour Temperature	3000K Warm White
Lumens	97 lm
Lumens Per Watt	97 lm/W

The **Crystal Starlite** is a decorative LED downlight made from cut glass with a chrome finish base. When illuminated the different facets cast a pattern of light back on to the surface into which the downlight is recessed. The result is a stylish and elegant lighting effect.

The fitting comes with a ceiling spring for fixing into plaster board. A burial tube is supplied for recessing into more solid material, such as brick or concrete.

An LED driver is needed to power this product.

### LED Driver Options

- Switching - Use this driver for on/off control. Cannot be used for dimming.
- Dimming - Normal - Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
- Dimming - 1-10V - Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.