



The **Gip Surface Extrusion Profile** comes in 1m, 2m or 3m lengths and is used to house our LED Tape, which keeps it safe and out of the way.

Can be used in conjunction with the **Teknik Extrusion** ideal for when recessing into plaster board.

This extrusion has been anodized.

Parts Required

Extrusions

As many lengths of extrusion can be used as is desired. Any 1m or 2m piece can be positioned end to end with each other to make an unlimited distance.

Endcap

An Endcap is required for each circuit of extrusions being used. It is positioned on the end of the very last extrusion in the circuit and is used to stop dust from and moisture from interfering with the electrical components.

Powerend

An Powerend is required for each circuit of extrusions being used. It is positioned on the very first extrusion in the circuit and serves the same purpose as the Endcap. The powerend has a hole in the centre which allows a cable to be fed through to power the strips.

Diffuser

A diffuser is used to give the light a more even blend. Simply purchase the same amount of diffusers as you did with extrusions.

Will fit any tape with a maximum width of 10mm.

Can be used in conjunction with the **Teknik Extrusion** ideal for when recessing into plaster board.

This extrusion has been anodized.

GIP ALU 1.07M

Aluminium 1070mm
Quicklink: Q3A32

General

Colour Aluminium
Construction Aluminium

Dimensions

Depth 7.5mm
Length 1070mm
Width 26mm