



LEDPANEL60LDIM W

3000K Warm White 60W Quicklink: Q39F0

General Colour Construction Dimmable IP Rating	Silver Aluminium Yes IP54
Dimmable LED Type Number of LED's Operating Temperature	Yes SMD3014 644 -20°C - +40°C
Dimensions Depth Length Width	13mm 1200mm 600mm
Electrical Maximum Wattage Voltage	60W 24V
Light Characteristic Beam Angle Colour Rendering	s 150° 80

Colour Rendering80IndexIndexColour Temperature3000K Warm WhiteHalogen Equivalent160WWattage5000 ImLumens5000 ImLumens Per Watt83 Im/W



The **LED Panel** range features the latest in LED technology. The panels are suitable for commercial and domestic applications, and are designed to fit directly into existing standard suspended ceilings and recesses, or can be suspended (fixings available separately). These panels are ideally suited for office lighting and for meeting rooms and corridors. Please note a 24V driver is required to power this product.

Key Features

- Energy savings up to 70%-80% compared to fluorescent equivalent
- Instant start, no flickering or humming
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Made with constant current LED tape that can work under unstable voltage.
- Compatible with RF, Dali, DMX512, 0-10V Dimmers
- No electric wave
- Excellent thermal management and refined aluminium
- Mercury free
- No RF interference