



## **LEDPANEL60LDIM C**

4000K Cool White 60W Quicklink: Q39EF

General

Colour Silver

Construction Aluminium

Dimmable Yes
IP Rating IP54

Dimmable Yes

LED Type SMD3014

Number of LED's 644

Operating -20°C - +40°C

Temperature

Dimensions

Depth 13mm Length 1200mm Width 600mm

Electrical

Maximum Wattage 60W Voltage 24V

**Light Characteristics** 

Beam Angle 150° Colour Rendering 80

Index

Colour Temperature 4000K Cool White

Halogen Equivalent 160W

Wattage

Lumens Per Watt 5000 lm 83 lm/W

The **LED Panel** range features the latest in LED technology. The panels are suitable for commercial and domestic applications, and are designed to fit directly into existing standard suspended ceilings and recesses, or can be suspended (fixings available separately). These panels are ideally suited for office lighting and for meeting rooms and corridors. Please note a 24V driver is required to power this product.

## **Key Features**

- Energy savings up to 70%-80% compared to fluorescent equivalent
- Instant start, no flickering or humming
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Made with constant current LED tape that can work under unstable voltage.
- Compatible with RF, Dali, DMX512, 0-10V Dimmers
- No electric wave
- Excellent thermal management and refined aluminium
- Mercury free
- No RF interference