

# LED Panel

LED Panel Light 24V 600 x 300mm  
3000K 34W



**MR. RESISTOR®**  
Lighting Specialist Est. 1968



## LED PANEL 34W/WW

3000K 34W

Quicklink: Q3F70

### General

Colour	Silver
Construction	Aluminium
Dimmable	Yes
IP Rating	IP54

Dimmable	Yes
LED Type	SMD3528
Number of LED's	322
Operating Temperature	-20°C - +40°C

### Dimensions

Depth	13mm
Length	600mm
Width	300mm

### Electrical

Maximum Wattage	34W
Voltage	24V

### Light Characteristics

Beam Angle	150°
Colour Rendering Index	90
Colour Temperature	3000K Warm White
Halogen Equivalent Wattage	75W
Lumens	2900 lm
Lumens Per Watt	85 lm/W

The **LED Panel** range features the latest in LED technology. The panels are suitable for commercial and domestic applications, and are designed to fit directly into existing standard suspended ceilings and recesses, or can be suspended (fixings available separately). These panels are ideally suited for office lighting and for meeting rooms and corridors. Please note a 24V driver is required to power this product.

### Key Features

- Energy savings up to 70%-80% compared to fluorescent equivalent
- Instant start, no flickering or humming
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Made with constant current LED tape that can work under unstable voltage.
- Compatible with RF, Dali, DMX512, 0-10V Dimmers
- No electric wave
- Excellent thermal management and refined aluminium
- Mercury free
- No RF interference
- Compatible with 2.4G controller