



LEDPANEL 34W/CW

4000K 34W Quicklink: Q3F6F

General

Colour Silver

Construction Aluminium

Dimmable Yes IP Rating IP54

Dimmable Yes

LED Type SMD3528

Number of LED's 322

Operating -20°C - +40°C

Temperature

Dimensions

Depth 13mm Length 600mm Width 300mm

Electrical

Maximum Wattage 34W Voltage 24V

Light Characteristics

Beam Angle 150° Colour Rendering 90

Index

Colour Temperature 4000K Cool White

Halogen Equivalent 75W

Wattage

Lumens Per Watt 2900 lm 85 lm/W The **LED Panel** range features the latest in LED technology. The panels are suitable for commercial and domestic applications, and are designed to fit directly into existing standard suspended ceilings and recesses, or can be suspended (fixings available separately). These panels are ideally suited for office lighting and for meeting rooms and corridors. Please note a 24V driver is required to power this product.

Key Features

- Energy savings up to 70%-80% compared to fluorescent equivalent
- Instant start, no flickering or humming
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Made with constant current LED tape that can work under unstable voltage.
- Compatible with RF, Dali, DMX512, 0-10V Dimmers
- No electric wave
- Excellent thermal management and refined aluminium
- Mercury free
- No RF interference
- Compatible with 2.4G controller