





LEDPANEL 30W CCT

Colour Temp Adjustable 2500K-7000K 30W Quicklink; Q39EA

\sim	 _	- ·	

Colour Silver
Construction Aluminium
Dimmable Yes
IP Rating IP54

Dimmable Yes
LED Type SMD3528
Number of LED's 384
Operating Temperature -20°C -

+40°C

Dimensions

Depth 13mm Length 600mm Width 600mm

Electrical

Maximum Wattage 30W Voltage 24V

Light Characteristics

Beam Angle 150°
Colour Rendering Index 90
Halogen Equivalent 75W
Wattage

Lumens 2400 lm Lumens Per Watt 80 lm/W The **LED Panel** range features the latest in LED technology. The panels are suitable for commercial and domestic applications, and are designed to fit directly into existing standard suspended ceilings and recesses, or can be suspended (fixings available separately). These panels are ideally suited for office lighting and for meeting rooms and corridors. Please note a 24V driver is required to power this product.

Key Features

- Energy savings up to 70%-80% compared to fluorescent equivalent
- Instant start, no flickering or humming
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Made with constant current LED tape that can work under unstable voltage.
- Compatible with RF, Dali, DMX512, 0-10V Dimmers
- No electric wave
- Excellent thermal management and refined aluminium
- Mercury free
- No RF interference
- Compatible with 2.4G controller