







## **LEDPANEL SMB 30W CCT**

Colour Temp Adjustable 2500K-7000K 30W Quicklink: Q4159

General

Colour Black Aluminium Construction Dimmable Yes

Dimmable Yes

LED Type SMD3528 Number of LED's 384

Operating Temperature -20°C - +40°C

Dimensions

Depth 80mm 600mm Length Width 600mm

Electrical

Maximum Wattage 30W Voltage 24V

Light Characteristics

Beam Angle 150° Colour Renderina Index Lumens 2400 lm Lumens Per Watt 80 lm/W The LED Surfaced Panel Light Box range features the latest in LED technology. The panels are suitable for commercial and domestic applications, included with the LED Panel is a surfaced mounting box for ceilings in which panels can't be recessed into the ceiling. These panels are ideally suited for office lighting and for meeting rooms and corridors.

This kit includes a 24V driver and a CCT adjustable touch panel controller, dimmable drivers are available as additional option.

## **Key Features**

- Energy savings up to 70%-80% compared to fluorescent equivalent
- Instant start, no flickering or humming
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Made with constant current LED tape that can work under unstable voltage.
- Compatible with RF, Dali, DMX512, 0-10V Dimmers
- No electric wave
- Excellent thermal management and refined aluminium
- Mercury freeNo RF interference
- Compatible with 2.4G controller

t: +44 (0)20 8874 2234 f: +44 (0)20 8871 2262 www.mr-resistor.co.uk