



LEDPANEL SMS 34W CW

4000K Cool White 34W Quicklink: Q4155

General

Colour Silver
Construction Aluminium
Dimmable Yes

Dimmable Yes

LED Type SMD3014

Number of LED's 322

Operating -20°C - +40°C

Temperature

Dimensions

Depth 80mm Length 600mm Width 600mm

Electrical

Maximum Wattage 34W Voltage 24V

Light Characteristics

Beam Angle 150° Colour Rendering 80

Index

Lumens Per Watt 2800 lm Lumens Per Watt 82 lm/W The **LED Surfaced Panel Box** range features the latest in LED technology. The panels are suitable for commercial and domestic applications, included with the LED Panel is a surfaced mounting box for ceilings in which panels can't be recessed into the ceiling. These panels are ideally suited for office lighting and for meeting rooms and corridors. Please note a 24V driver is included with this kit, dimmable drivers are available as additional option.

Key Features

- Energy savings up to 70%-80% compared to fluorescent equivalent
- Instant start, no flickering or humming
- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Made with constant current LED tape that can work under unstable voltage.
- Compatible with RF, Dali, DMX512, 0-10V Dimmers
- No electric wave
- Excellent thermal management and refined aluminium
- Mercury free
- No RF interference