



MICRO PLUS AN1M

Anodised Aluminium 1000mm
Quicklink: Q2F39

General

Colour	Aluminium
Construction	Anodised Aluminium

Dimensions

Depth	6mm
Length	1m
Width	15.2mm

Key Features

- Minimum dimensions for LED strips 0.39" / 10 mm wide
- Simple assembly
- Versatile application
- Low weight
- Good heat transfer in relation to the surface
- Designed to reach an IP67 waterproof rating

Parts Required

Extrusions

As many lengths of extrusion can be used as is desired. Any 1m or 2m piece can be positioned end to end with each other to make an unlimited distance.

Endcap

An Endcap is required for each circuit of extrusions being used. It is positioned on the end of the very last extrusion in the circuit and is used to stop dust from and moisture from interfering with the electrical components.

Powerend

An Powerend is required for each circuit of extrusions being used. It is positioned on the very first extrusion in the circuit and serves the same purpose as the Endcap. The powerend has a hole in the centre which allows a cable to be fed through to power the strips.

Diffuser

A diffuser is used to give the light a more even blend. Simply purchase the same amount of diffusers as you did with extrusions.

Micro LED Extrusion Profile - Cabinet and Cove

Micro Surface LED Tape Extrusion Profile
Anodised Aluminium 1000mm



MR. RESISTOR®
Lighting Specialist Est. 1968

Will fit any tape with a maximum width of 10mm.

This extrusion has been anodized.

