


Phantom Round LED

Phantom Bronze Round Uplight 8° 700mA
3000K Warm White 3W



MR. RESISTOR®
Lighting Specialist Est. 1968



AL2118 RD BRZ WW

3000K Warm White 3W
Quicklink: Q3F2F

General

Colour	Bronze
Construction	Bronze / Glass
Dimmable	Yes
IP Rating	IP68

Dimmable	Yes
LED Type	High Power

Dimensions

Cable Length	2m
Cut Out	40mm (Diameter)
Depth	80mm
Diameter	48mm
Tube Diameter	49mm
Tube Length	88mm

Electrical

Amperage	700mA
Maximum Wattage	3W
Requires Driver	Yes

Light Characteristics

Beam Angle	8°
Colour Rendering Index	80
Colour Temperature	3000K Warm White
Lumens	130 lm
Lumens Per Watt	43 lm/W

The **Phantom Round 8°** is a small recessed uplight that can be used in floors and walls. It is rated IP68, allowing it to be fitted into wet areas such as shower cubicles or outside in decking. It can be placed in zones 0, 1 and 2 of bathrooms, offering full flexibility in its placement. Constructed from marine grade steel and frosted glass.

The fitting comes complete with spring clips to mount into hollow walls and floors. It also comes with a plastic mounting box for use with brick and other solid surfaces. If used outside, it is strongly advised that *Heat Shrink* is used to protect the wiring from water.

Please note; this product requires a 700mA driver and must be wired in series.

LED Driver Options

- Switching - Use this driver for on/off control. Cannot be used for dimming.
- Dimming - Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
- Dimming - 1-10V - Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.

Phantom Round LED

Phantom Bronze Round Uplight 8° 700mA
3000K Warm White 3W



MR. RESISTOR[®]
Lighting Specialist Est. 1968

