





AL2118 RD PS RGB

RGB 3W Quicklink: Q416A

General

Colour Polished Steel
Construction Steel / Plastic
Dimmable Yes

Dimmable Yes IP Rating IP68

Dimmable Yes

LED Type High Power

Dimensions

Cable Length 500mm

Cut Out 40mm (Diameter)

Depth 82mm
Diameter 49mm
Tube Diameter 49mm
Tube Length 88mm

Electrical

Amperage 350mA
Maximum Wattage 3W
Requires Driver Yes

Light Characteristics

Beam Angle 38°

The **Phantom Round 40° RGB** is a small recessed uplight that can be used in floors and walls. It is rated IP68, allowing it to be fitted into wet areas such as shower cubicles or outside in decking. It can be placed in zones 0, 1 and 2 of bathrooms, offering full flexibility in its placement. Constructed from marine grade steel and frosted glass.

The fitting comes complete with spring clips to mount into hollow walls and floors. It also comes with a plastic mounting box for use with brick and other solid surfaces. If used outside, it is strongly advised that *Heat Shrink* is used to protect the wiring from water.

This light does not require any wiring as it is a uses the plug and play system. The power cable and endcap will be needed to be connected to make the light work.

The minimum required products needed to operate multiple fittings are:

WISERGB 350MA M: Wise Chameleon Master

SPEC ENDCAP: End CapRS2524: LED DriverSPECPC1: Power Cord

• Wise 7 Channel Switch or Wise 7 or 42 Channel Remote