





AL2118 RD SS BLU

Blue 3W Quicklink: Q4139

General

Colour Stainless Steel Construction Steel / Glass

Dimmable Yes **IP Rating IP68**

Dimmable Yes

LED Type High Power

Dimensions

Cable Length 2m

Cut Out 40mm (Diameter)

Depth 80mm 48mm Diameter Tube Diameter 49mm Tube Length 88mm

Electrical

Amperage 700mA Maximum Wattage 3W Requires Driver Yes

Light Characteristics

8° Beam Angle

The **Phantom Round 8°** is a small recessed uplight that can be used in floors and walls. It is rated IP68, allowing it to be fitted into wet areas such as shower cubicles or outside in decking. It can be placed in zones 0, 1 and 2 of bathrooms, offering full flexibility in its placement. Constructed from marine grade steel and frosted glass.

The fitting comes complete with spring clips to mount into hollow walls and floors. It also comes with a plastic mounting box for use with brick and other solid surfaces. If used outside, it is strongly advised that *Heat Shrink* is used to protect the wiring from water.

Please note; this product requires a 700mA driver and must be wired in series.

LED Driver Options

- Switching Use this driver for on/off control. Cannot be used for dimming.
- Dimming Use this driver for dimming control. Some dimmers may require a resistive dummy load to meet the minimum load requirements.
- Dimming 1-10V Use this driver with a 1-10V dimmer modules or control systems. This type of dimming does not have a minimum load.





