



SLFM360

White 2000W Quicklink: Q1D0D

General

| Colour | White |
|--------------|---------|
| Construction | Plastic |
| IP Rating | IP44 |
| | |

Dimensions

| Cable Length | 1m |
|--------------------------------------|-----------------|
| Cut Out | 75mm (Diameter) |
| Depth | 84mm |
| Diameter | 84mm |
| Electrical Maximum Wattage | 2000/4/ |

Maximum Wattage2000WVoltage240V AC

The **360° PIR Flush Mounted Occupancy Switch** utilises passive infrared technology to detect heat from a moving person. Upon detection, the attached lighting load will illuminate for a user-determined time period between five seconds and eighteen minutes. An integral daylight sensor ensures all day or night-only operation.

The connected load must not exceed maximum 2000W filament/incandescent or 500W fluorescent/low energy lighting. It is not suitable for use with discharge lighting.

The package includes a PIR Sensor unit, instruction manual, and accessory pack. This consists of a wiring cover, 2 x cable clamps, 4 x clamp screws, and 1 x lens mask sticker. For more information, please click on the downloads tab.

Features

- 360° ceiling flush mount PIR presence detector
- 6m diameter (3m radius) detection range at 2.5m mounting height
- Light ON time adjustable from 5 seconds to 18 minutes
- Manual ON/OFF override
- IP44 weatherproof rating (also suitable for outdoor use)
- Adjustable light level control
- Total PIR switching: 2000W (incandescent or halogen, 500W fluorescent/low energy lighting). Not suitable for use with discharge lighting