



## REGULOR 2M ANOD

Anodised Aluminium 2000mm

Quicklink: Q3A46

### General

Colour	Aluminium
Construction	Aluminium

### Dimensions

Depth	12mm
Length	2m
Width	16mm

The **Regulor Surface Extrusion Profile** comes in 1m or 2m lengths and is used to house our LED tape, which keeps the tape light safe and out of the way. The Regulor features an adjustable insert that effects the beam angle of the tape. 10° (without insert), 30°, 60°, 90° can be achieved depending on where the plate is positioned.

### Parts Required

#### Extrusions

As many lengths of extrusion can be used as is desired. Any 1m or 2m piece can be positioned end to end with each other to make an unlimited distance.

#### Endcap

An Endcap is required for each circuit of extrusions being used. It is positioned on the end of the very last extrusion in the circuit and is used to stop dust from and moisture from interfering with the electrical components.

#### Powerend

An Powerend is required for each circuit of extrusions being used. It is positioned on the very first extrusion in the circuit and serves the same purpose as the Endcap. The powerend has a hole in the centre which allows a cable to be fed through to power the strips.

#### Diffuser

A diffuser is used to give the light a more even blend. Simply purchase the same amount of diffusers as you did with extrusions.

Will fit any tape with a maximum width of 10mm.

This extrusion has been anodized.

## Product Installation Video

# Regular LED Extrusion Profile - Cabinet and Cove

Regular Surface LED Tape Extrusion Profile  
Anodised Aluminium 2000mm



**MR. RESISTOR**<sup>®</sup>  
Lighting Specialist Est. 1968

