

Uplighters - Recessed



83



## Midi Halogen

- The Midi Halogen is a 12V waterproof IP66 uplighter. It has a stainless steel bezel with frosted glass. It requires a standard 12V transformer and a 12V MR16 lamp (35W max).
- The Midi Halogen is suitable for using both for the exterior or interior of a property.

Maximum Wattage	35W
_ampholder	GU5.3
Diameter	100mm
Depth	110mm
Cut Out	90mm
P Rating	IP66
/oltage	12V

#### Accessories

PICO SUPER 60	Transformer Electronic
	Black 60W
ET60	Waterproof Transforme
	Electronic Black 60W
MARCH CONJUSTANT	11.1 50

M281 CONSTANT Halogen 50mm (Constant Colour) 35W 40°



#### Available Finishes

stainless steel (A4002 SAT-STL)



## Mini Halogen

- The Mini Halogen is a halogen 12V waterproof IP65 uplighter. It requires a standard 12V transformer and a 12V MR11 lamp.
- The Mini Halogen is suitable for using both for the exterior or interior of a property.

Maximum Wattage	20W
Lampholder	GU4
Diameter	65mm
Depth	75mm
Cut Out	55mm
IP Rating	IP65
Voltage	12V

#### Accessories

PICO SUPER 60	Electronic Black 60W
AH/AL TUBE	Burial Tube 2112/3004
M251G	Halogen 35mm 20W 17°
M252G	Halogen 35mm 20W 10°
ET60	Waterproof Electronic
	Block COW



### Available Finishes

- clear glass (AH2112 SILVER/CL)
- frosted glass (AH2112 SILVER/FR)



Square Phantom

- The Phantom is a small recessed uplight that can be used in floors and walls. The phantom is rated IP68, this allows it to be fitted into wet areas.
- The phantom comes complete with spring clips to mount into hollow walls and floors. It also comes with a plastic mounting box for use with brick and other solid surfaces.

Wattage	3W
Length	48mm
Width	48mm
Depth	82mm
Cut Out	40mm
Amperage	700mA
IP Rating	IP68
Requires Driver	Yes
Beam Angle	45°
Lifespan	50,000 hours

#### Accessories

PTDCC10350MA	LED Driver White 10W
	350mA (Required)





### Available Finishes

- stainless steel, warm white (AL2118 3W SS W/W)
- stainless steel, cool white (AL2118 3W SS C/W)



# Phantom

- The Phantom is a small recessed uplight that can be used in floors and walls. The phantom is rated IP68, this allows it to be fitted into wet areas, for example a shower cubicle or outside in decking.
- The phantom comes complete with spring clips to mount into hollow walls and floors. It also comes with a plastic mounting box for use with brick and other solid surfaces.

Wattage	1W
Diameter	49mm
Depth	82mm
Cut Out	40mm
Amperage	350mA
IP Rating	IP68
Requires Driver	Yes
Beam Angle	8°
Lifespan	50,000 hours

#### Accessories

PTDCC10350MA LED Driver White 10W 350mA (Required)





### Available Finishes

- warm white (AL2118 NB SS W/W)
- cool white (AL2118 NB SS C/W)
- amber (AL2118 NB SS AMB)
- blue (AL2118 NB SS BLU)



# Battlestar Uplight recessed uplighter

- The Battlestar Uplight is a recessed uplight that can be used in floors and walls.
- The Battlestar Uplight is rated IP65, this allows it to be fitted into wet areas, for example outside in decking.
- ☐ The fitting has a built in power

Maximum Wattage Fitting Height Head Diameter Voltage Depth IP Rating Base Diameter Beam Angle

Available Finishes





LED Miniature Square

### Accessories

Lifespan

BULL 350mA 6W	LED Driver White 6W
WISERGB	350mA
350MA M	Wise Chameleon Master
ZT2099	350mA 21W
GLASS/FR	Frosted Glass Lense

















# LED Miniature recessed uplighter

- The LED Miniature Square Uplighter is a small recessed LED suitable for uplighting or low level lighting, for indoor or outdoor use.
- The long life LED makes this fitting great for subtle lighting in the garden or the home. It has an IP rating of IP65, making it suitable for use in gardens or decking.

1W Height Diameter Depth 64mm Cut Out 46mm Amperage 350mA IP Rating IP65 Luxeon Type of LED 50,000 hours

D Driver White 6W	BULL 350mA 6W	LE
mA		350
e Chameleon Master	WISERGB	Wis
mA 21W	350MA M	350
stad Glass Lanca	ZT2099	Fro



# Available Finishes

Accessories







## Nail recessed uplighter

Wattage

Diameter

Cut-Out

Voltage

IP Rating

Accessories

DC1024VLS

Height

The Nail Uplighter is ideal for fitting

diameter. It is IP65 rated so it can

be located internally or externally.

minimal amount of ambient light.

Blue, Green, Red and White.

It is a small guide light that gives a

It is available in five colours: Amber,

0.5W

42mm

10mm

IP65

LED Driver White

10W 24V

24V DC

in small spaces with its 12mm

- The LED Miniature Round Uplighter is a small recessed LED suitable for uplighting or low level lighting, for indoor or outdoor use.
- The long life LED makes this fitting great for subtle lighting in the garden or the home. It has an IP rating of IP65, making it suitable for use in gardens or decking.

Maximum Wattage 1W 52mm 56mm 64mm 46mm 350mA IP65 Luxeon Lifespan 50,000 hours

D Driver White 6W 0mA ise Chameleon Master 0mA 21W Frosted Glass Lense

GLASS/FR



## Available colours

white (AL2110W1 ALUM)

amber (AL2110A1 ALUM)

blue (AL2110B1 ALUM)

green (AL2110G1 ALUM)

red (AL2110R1 ALUM)

