



BLOB BF2815/EMERG

25° 4000K Cool White
Quicklink: Q45FB

General	
Colour	White
Construction	Aluminium
Dimmable	No
Battery	
Battery	3 hrs
Emergency Type	Maintained
Dimensions	
Cut Out	100mm (Diameter)
Diameter	122mm
Minimum Ceiling Depth	106mm
Electrical	
Maximum Wattage	9W
Voltage	240V
Light Characteristics	
Beam Angle	25°
Colour Temperature	4000K Cool White

The **Blob** is a high powered LED downlight with a silver reflector. A LED driver is wired into the fitting, simply wire to mains.

The **Blob** range of fittings are light weight simplifying installation. This fitting is not dimmable.

This kit includes the **Blob Downlight LED Emergency Pack** which is a maintained, fireproof emergency pack compatible with the Blob Downlight (switched) range.

Emergency packs are used in commercial buildings as a safety precaution during a power outage, so that people will be able to find their way out of a building in the event of an emergency.

This is a maintained emergency pack.

Maintained Emergency Lighting: The emergency light units are illuminated at all times using the same lamps for both normal and emergency operation. Please note maintained fittings can be wired as non-maintained.

Non-Maintained Emergency Lighting: A non-maintained fitting is not illuminated until the event of power failure.