



COPIR IP66BK

Black 1500W
Quicklink: Q53C9

General

| | |
|--------------|---------|
| Colour | Black |
| Construction | Plastic |
| IP Rating | IP66 |

Dimensions

| | |
|--------|------|
| Height | 37mm |
| Length | 75mm |
| Width | 60mm |

Electrical

| | |
|-----------------|-------|
| Maximum Wattage | 1500W |
| Voltage | 240V |

The **Compact Person Detector Switch** will switch outdoor lights on when a person approaches. Welcomes friends and deters intruders. Ideal for security and convenience. A compact design for controlling new or existing outdoor lights.

Features

- The COPD is suitable for external mounting
- The maximum load must not exceed 6 amps of resistive load or 4 amps of inductive, fluorescent or discharge load, with a 230VAC supply.
- The switch will turn the lights on for between 2 to 20 minutes according to the setting of the vertical adjuster spindle inside the housing.
- Whenever a person is detected the timer always starts again from the beginning of the set time lag.
- The Photocell can be set so that lights do not switch on during the day.
- Compact polycarbonate housing.

Loading

- Up to 6 amps (1500W) of incandescent or mains halogen lamps.
- Up to 4 amps (1500W) of electronic and wire wound transformers, fluorescent lamps (high frequency or switch start).
- Up to 2 amps (500W) of CFL, LED Drivers and LED lamps and fittings.
- Up to 1 amp (250W) of fans.