





The **50mm Fixed Downlighter** holds a 50mm lamp. The downlighter uses a spring retention system for easy installation and lamp changing.

This fitting is rated IP54 and can, therefore, be used in a bathroom.

Please note: the ceiling depth for this downlight depends on the lamp choice. For a standard halogen GU10 lamp, the depth is 85mm. For an LED GU10 lamp a ceiling depth of 115mm should be allowed. This is a Fire-Rated Downlight.

The **Reality GU10 LED 7W** Lamp is equivalent to a 75W GU10 halogen lamp and, like a halogen lamp, is dimmable.

Key Features

- Complies with October 2010 Part L regulations
- Fully dimmable with leading edge dimmers
- Fire-Rated Downlight
- Lifetime of 25,000 hrs

FMR3025 WCL/R45D3K

7W (=75W) 45° Quicklink: Q3BBC

General

Cap GU10
Colour White
Construction Die-Cast

Aluminium

Dimmable Yes IP Rating IP54

Dimmable Yes

Dimensions

Cut Out 62mm (Diameter)

Diameter 70mm Minimum Ceiling Depth 120mm

Electrical

Energy Efficiency Rating A
Maximum Wattage 7W
Power Factor 0.95
Voltage 240V

Light Characteristics

Beam Angle 45° Colour Rendering Index 80

Colour Temperature 3000K Warm

White 75W

Halogen Equivalent

Wattage

Lumens Per Watt 630 lm 90 lm/W

t: +44 (0)20 8874 2234 f: +44 (0)20 8871 2262 www.mr-resistor.co.uk