



Downlighters, if not safely protected, can become a fire hazard as the hole cut in the ceiling to accommodate them compromises its fire resistance. Current building and wiring regulations have meant firehoods have become a necessity. Not only does a **Grid & Grid Trimless AR70/MR16 Firehood** seal to stop fire penetration into the ceiling void left by fittings for up to one hour, but in normal use also offer ventilation to prevent the light fitting from overheating.

Please note that this firehood has been especially designed for use with a *Grid/Grid Trimless Double Downlighter (AR70 and MR16 types)* shown on the right. Fire protection cannot be guaranteed if used with other products.

Product Features:

- Reduce sound penetration
- · Lightweight, easy to install with no extra support
- · Can be fitted from below
- Not affected by moisture (rot proof)
- Maintenance free
- Economical

Please note that all dimensions of firehoods are approximate due to their flexible material construction.

FRT200 MR16HOOD

300mm x 190mm Up to 1 hour Quicklink: Q1E81

General

Cap GU10 / AR70,GU5.3 /

MR16

Construction Patented Fire Rated

Fabric

100mm

Fire Protection Up to 1 hour

Dimensions

Downlight

Height

Downlight 216mm

Length

Downlight 110mm

Width

Height 125mm Length 300mm Width 190mm

t: +44 (0)20 8874 2234 f: +44 (0)20 8871 2262 **www.mr-resistor.co.uk**