



## EI630RF HEAT

Lithium Battery Wireless Quicklink: Q4D42

## General

Colour	White
Construction	Plastic
Dimensions	
Diameter	115mm
Height	55mm

The **Ei603RF** Battery Heat alarm with RadioLink is activated by head from fire, not smoke, which makes it ideal for kitchen installations where smoke alarms are prone to nuisance alarms.

The Ei630RF is powered by a sealed 10-Year lithium battery that is non-replaceable. It is designed to last for the working life of the alarm. When depleted it will give an audible visual warning.

The Ei630RF is fitted with a RadioLink Module. This will allow the alarm to be interconnected to other RadioLink and Smart Link Alarms and Devices. Up to 12 Alarms and devices can be interconnected. An interconnected system will enhance early detection and warning of fire.

The Ei630RF is supplied with screw fittings with a simple install twist on mounting base. The alarm is not powered until it is twisted on the mounting base, thus avoiding the battery power consumption during storage and prior to installation.

The Ei630RF and other RadioLink enabled smoke Alarms and Devices must be House Coded together. This will avoid interference and unintentional interconnection with other systems.

The Alarm is fitted with a large central Test/Hush button to facilitate frequent testing of the Alarm and system. The silence function allows the Alarm/System to be silenced in the case of false/ nuisance alarm, e.g. Cooking fumes.

- Battery powered with a sealed 10-year lithium battery
- Fast response thermistor sensor, best for large flaming fires
- RadioLINK Module fitted for wireless interconnection
- Up to 12 RadioLINK & SmartLINK Alarms or Devices can be interconnected
- Easy to install, no wiring
- Large easy to use Test/Hush button
- Silence nuisance/false alarms
- Built in piezoelectric horn
- Alarm fault warnings
- Aesthetically pleasing, compact design
- 10yr life