





LEDPANEL SMB 34W WW/EMERG

3000K Warm White 34W Quicklink: Q461A

General

Colour Black
Construction Aluminium
Dimmable No

Dimmable No LED Type SMD3014 Number of LED's 322

Operating -20°C - +40°C

Temperature
Dimensions

Depth 80mm Length 600mm Width 600mm

Electrical

Maximum Wattage 34W Voltage 24V

Light Characteristics

Beam Angle 150° Colour Rendering 80

Index

Colour Temperature 3000K Warm White

Lumens Per Watt 2800 lm 82 lm/W

Included in this kit is the **LED Panel Emergency Pack**, which is a maintained emergency pack compatible with the majority of the LED panel range.

Please note: This is not dimmable.

Emergency packs are used in commercial buildings as a safety precaution during a power outage, so that people will be able to find their way out of a building in the event of an emergency.

Maintained Emergency Lighting: The emergency light units are illuminated at all times using the same lamps for both normal and emergency operation. Please note maintained fittings can be wired as non-maintained.

Non-Maintained Emergency Lighting: A non maintained fitting is not illuminated until the event of power failure.

The **LED Panel Light Box** range features the latest in LED technology. The panels are suitable for commercial and domestic applications, included with the LED Panel is a surfaced mounting box for ceilings in which panels can't be recessed into the ceiling. These panels are ideally suited for office lighting and for meeting rooms and corridors.

Kev Features

- Energy savings up to 70%-80% compared to fluorescent equivalent
- Instant start, no flickering or humming
- Complies with October 2010 Part L regulations
- Made with constant current LED tape that can work under unstable voltage.
- No electric wave
- Excellent thermal management and refined aluminium
- Mercury free
- No RF interference