

# Architectural LED

LED Recessed Uplight 45° 240V  
3000K Warm White 26W



**MR. RESISTOR®**  
Lighting Specialist Est. 1968



## HLE06401 45D W/W

3000K Warm White 26W

Quicklink: Q32B7

### General

Colour	Stainless Steel
Construction	Aluminium
Dimmable	No
IP Rating	IP67

Dimmable	No
Drive-Over Limits	20,000N
LED Type	Cree XP
Number of LED's	15
Operating Temperature	-20°C ~ +60°C

### Dimensions

Cable Length	3m
Cut Out	190mm (Diameter)
Depth	248mm
Diameter	193mm

### Electrical

Maximum Wattage	26W
Requires Driver	No

### Light Characteristics

Beam Angle	45°
Colour Temperature	3000K Warm White
Lumens	1750 lm
Lumens Per Watt	67 lm/W

The **Architectural LED Recessed Uplight** is a recessed uplight that can be driven over and used in commercial or domestic applications.

The Architectural Uplight is rated IP67, this allows it to be fitted into wet areas, for example outside in decking. The body of this fitting is made of high-pure die cast aluminium ZL102; the surface is finished with electrostatic powder coating, thermostatic hardening.

A LED driver is built into the fitting, simply wire to mains supply.