MR. RESiSTOR®
Lighting Specialist Est. 1968

ROPELED RED

Red 8W per Cut / 2 metre Cut
Quicklink: Q4C39

General

IP Rating	IP44
LED Chip	SMD 5050
LED per Tape	60 per cut length

Dimensions

Cut Length	2m
Diameter	13mm
Length	2m

Electrical

Maximum Wattage	8W
Voltage	240V

Light Characteristics

Lumens	500 lm
Lumens Per Metre	250 lm/m
Lumens Per Watt	63 lm/W
Watts Per Metre	4 W/m

LED Ropelight 5050 has many benefits over standard ropelight. The advantages include 50,000 hours life, a bright and sharp light source and low power consumption with virtually no heat. This means that it can safely be rebated instead of being surface mounted.

LED Ropelight 5050 has high visibility, making it ideal for use on buildings, signs and gardens. It also gives a subtle glow of light that is ideal for mounting into shelves, under cabinets and coving.

This fitting has a waterproof rating of IP44 only when both ends are sealed. This can be achieved by using strong special waterproof glue or silicon. It is attached to a power connector lead at one end and a end cap or coupler is fitted at the other end.

Please note that LED Ropelight 5050 can only be cut on the unit length. The maximum continuous length that can be cut is 100m. The price quoted is per unit length.

Features:

- High lumens output
- Eco friendly material
- Low power consumption
- Suitable for indoor & outdoor use
- Ultra flexible & unbreakable light body
- UV stabilizers material reduces rate of weathering

Please Note: Once Ropelight is it cut cannot be returned.

MR. RESiSTOR®
Lighting Specialist Est. 1968

13mm

t: +44 (0)20 8874 2234   e: info@mr-resistor.co.uk   www.mr-resistor.co.uk