

LED Ropelight 5050 has many benefits over standard ropelight. The advantages include 50,000 hours life, a bright and sharp light source and low power consumption with virtually no heat. This means that it can safely be rebated instead of being surface mounted.

LED Ropelight 5050 has high visibility, making it ideal for use on buildings, signs and gardens. It also gives a subtle glow of light that is ideal for mounting into shelves,

This fitting has a waterproof rating of IP44 only when both ends are sealed. This can power connector lead at one end and a end cap or coupler is fitted at the other end.

This fitting ties a be achieved by using strong species. power connector lead at one end and a end cap or coop.

Please note that LED Ropelight 5050 can only be cut on the unit length. The maximum continuous length that can be cut is 100m. The price quoted is per unit length.

- High lumens output
- Eco friendly material
- Low power consumption
- Suitable for indoor & outdoor use
- Ultra flexible & unbreakable light body
- UV stabilizers material reduces rate of weathering

Please Note: Once Ropelight is cut it cannot be returned.

## ROPELED COOL/W

White 8W per Cut / 2 metre Cut Quicklink: Q4C37

General

IP Rating IP44

LED Chip SMD 5050 LED per Tape 60 per cut length

**Dimensions** 

Cut Length 2<sub>m</sub> 13mm Diameter Length 2m

Electrical

Maximum Wattage 8W 240V Voltage

Light Characteristics

Watts Per Metre

6000K Daylight Colour Temperature Lumens 500 lm Lumens Per Metre 250 lm/m Lumens Per Watt 63 lm/W

4 W/m



