

# Fire Hoods

Standard Firehood

180mm Up to 1 hour



**MR. RESISTOR**<sup>®</sup>  
Lighting Specialist Est. 1968



## HOOD DLC4

180mm Up to 1 hour

Quicklink: Q1150

### General

Construction	Patented Fire Rated Fabric
--------------	----------------------------

Fire Protection	Up to 1 hour
-----------------	--------------

### Dimensions

Downlight Diameter	160mm
Downlight Height	130mm
Height	130mm
Length	180mm
Width	180mm

Downlighters, if not safely protected, can become a fire hazard as the hole cut in the ceiling to accommodate them compromises its fire resistance. Current building and wiring regulations have meant fire hoods have become a necessity. Can be easily fitted from above or below in plasterboard or suspended ceilings. Not only does a **Standard Fire hood** seal to stop fire penetration into the ceiling void left by fittings for up to one hour, but in normal use also offer ventilation to prevent the light fitting from overheating. Tested to BS476 parts 22 & 23, achieving up to 240 minutes integrity.

### Product Features:

- Reduce sound penetration
- Lightweight, easy to install with no extra support
- Can be fitted from below
- Not affected by moisture (rot proof)
- Maintenance free
- Economical

Please note that all dimensions of fire hoods are approximate due to their flexible material construction.