



The **Weathersafe Vision Single Gang 2-Way Switch (DP)** is manufactured from tough, durable thermoplastic. It is intended for use in an outdoor environment, or one in which the protection provided by the range is required. It is rated IP66, for protection against water and dust. It will need to be fitted with waterproof cable or conduit entries to maintain their IP rating once installed.

For more information, please click on the downloads tab.

Features

- 20AX(fluorescent rated) 1 gang DP 2-way
- 4 × 20mm cable entries
- Earth terminal and loop terminal in back box
- Impact resistant housing

Specification

- Operating Temperature: 0°C to 40°C
- Type: DP Switch
- Rocker Switch Poles: 2
- Rocker Switch Rating: 20A
- IP Rating: IP66
- Fully Complies with: BS EN 60669 (isolating switches) and BS 3676 (switches)

TGVL05

1 Gang Grey Quicklink: Q1CB5

General

Colour Grey

Construction Thermoplastic

IP Rating IP66

Compliance BS EN 60669 & BS

3676

0°C ~ 40°C

Operating

Temperature

Dimensions

Depth 66mm Height 96mm Width 92mm

Electrical

Voltage 240V

t: +44 (0)20 8874 2234 f: +44 (0)20 8871 2262 www.mr-resistor.co.uk