Sensors Wired

Wired PIR Flush Mounted Occupancy Switch 240V

2 Channel



WISE CEFLPIR

2 Channel
Quicklink: Q36F4

General

Colour	White
Construction	Plastic
IP Rating	IP44

Detection Angle	360°
Detection Range	5m
Photocell Range	100 to 1000 lux
Time Delay	10 secs to 40 mins

Dimensions

Cable Length	2m
Cut Out	64mm (Diameter)
Diameter	72mm

Electrical

Amperage	6A
Input Voltage	240V
Output Voltage	240V

The **Wired PIR Sensor Kit 240V** is a **Wise Transmitter** with a wired **PIR Flush Mounted Occupancy Switch**. The Wise Transmitter enables the PIR to send wireless signals to any Wise Receiver. Ideal for when you cannot install any cables between your sensor and your lighting circuit.

The transmitter is small enough to be placed in many locations, for example, in the ceiling, in the wall either through it, behind a recessed light fitting or in a surfaced mounted fitting. The transmitter should be placed in a suitable insulated box.

It can be fitted into a small waterproof box to allowed it to be used outside for your garden lighting, garage doors and water features.

The transmitters are designed to be simple to install, easy to use and most importantly, reliable.

Wise Controls Introduction Video

